

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

- A. PRODUCT NAME : AGM Series Battery
- B. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE
  - : Electric Storage Battery.
- C. MANUFACTURER/SUPPLIER/DISTRIBUTOR INFORMATION
  - MANUFACTURER : Sebang Global Battery CO.,Ltd.

Namsan-dong 601-9, Changwon-city, Gyeongnam

TEL: +82-55-279-9734 FAX: +82-55-282-2658

#### 2. HAZARDS IDENTIFICATION

#### A. HAZARD CLASSIFICATION

PHYSICAL HAZARDS

: Not Classified.

#### HEALTH HAZARDS

	:	Acute toxicity	Category 4 (inhalation)
	:	Skin corrosion/irritation	Category 1
	:	Serious eye damage/eye irritation	Category 1
	:	Carcinogenicity	Category 1B
	:	Germ cell mutagenicity	Category 2
	:	Specific target organ toxicity – single exposure	Category 1
	:	Specific target organ toxicity – repeated exposure	Category 1
• • •			

### ENVIRONMENTAL HAZARDS

: Not Classified.

#### B. GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAMS



SIGNAL WORD : DANGER.

### HAZARD STATEMENTS

- H332 Harmful if inhaled.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H350 May cause cancer (inhalation).
- H341 Suspected of causing genetic defects.
- H370 Specific target organ toxicity single exposure; Respiratory tract irritation



 Causes damage to organs (Hematopoietic system, kidney, central nervous system, peripheral nervous system, cardiovascular system, immune system, respiratory).

:

## PRECAUTIONARY STATEMENTS

### [Prevention]

[Fievention]	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a wellventilated area.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P281	Use personal protective equipment as required.
P270	Do not eat, drink or smoke when using this product.
[Response]	
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P363	Wash contaminated clothing before reuse.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment (see on this label).
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P307+P311	IF exposed: Call a POISON CENTER or doctor/physician.
P314	Get medical advice/attention if you feel unwell.
[Storage]	
P405	Store locked up.
[Disposal]	
P501	Dispose of contents/container in accordance with local/regional/national regulations.
OTHER HAZARDS WHI	CH DO NOT RESULT IN CLASSIFICATION (e.g. Dust explosion hazards)
NFPA/HMIS Rating	
	Health=3, Flammability=0, Instability=1

(0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme)

C.



Chemical name / Synonym	CAS No. or ID	Content (%)
Lead	7439-92-1	67 - 70
Electrolyte (sulfuric acid / water / solution)	7664-93-9	24 - 25
Polypropylene / PP Resin	9003-07-0	4 - 5
Separator	Not available	2 - 3

\* European Inventory of Existing Commercial Chemical Substances (EINECS).

## 4. FIRST AID MEASURES

A. EYE CONTACT	:	If a battery ruptures, do not rub or scratch exposed eye. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. GET MEDICAL ATTENTION IMMEDIATELY.		
B. SKIN CONTACT	:	If a battery ruptures, do not rub or scratch exposed skin. If liquid get on the skin, immediately flush the contaminated skin with water for at least 15 minutes. If liquid penetrate through the clothing, immediately remove the clothing and shoes under a safety shower and continue to wash the skin for at least 15 minutes. GET MEDICAL ATTENTION IMMEDIATELY.		
C. INHALATION	:	If a battery ruptures, move to fresh air in case of accidental inhalation of mist. If breathing has stopped, perform artificial respiration. If breathing is difficult, give oxygen. GET MEDICAL ATTENTION AS SOON AS POSSIBLE.		
D. INGESTION	:	If solutions of a battery chemicals have been swallowed and the person is conscious, give one glass of water. Vomiting may occur spontaneously, but Do NOT induce vomiting. Never give anything by mouth to an unconscious person. GET MEDICAL ATTENTION IMMEDIATELY.		
E. MOST IMPORTANT	SYN	IPTOMS/EFFECTS, ACUTE OR DELAYED		
EYES	:	Not a likely route of exposure. If a battery ruptures, direct contact with the liquid or exposure to vapors or mists may cause tearing, redness, swelling, corneal damage and irreversible eye damage. Splashes in the eyes will cause severe burns.		
SKIN	:	Not a likely route of exposure. Direct contact with internal components of a battery can be severely irritating to the skin and may result in redness, swelling, burns and severe skin damage. Skin contact may aggravate an existing dermatitis condition.		
INHALATION	:	Not a likely route of exposure. If a battery ruptures, may be harmful or fatal if inhaled in a confined area. May cause severe irritation and burns of the nose, throat and respiratory tract.		
INGESTION	:	Not a likely route of exposure. Causes serious burns of the mouth or perforation of the esophagus or stomach. May be fatal if swallowed.		
* Lood move on vote to blood, bidneys, control nervous system (CNC). Depended or prolonged				

\* Lead may causes toxic to blood, kidneys, central nervous system (CNS). Repeated or prolonged exposure to lead can produce target organs damage.

F. INDICATION OF IMMEDIATE MEDICAL ATTENTION AND NOTES FOR PHYSICIAN



Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition.

### 5. FIRE FIGHTING MEASURES

- A. SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA
  - Use extinguishing media appropriate for surrounding fire.
  - If a battery ruptures, use dry chemical, soda ash, lime, sand or carbon dioxide.
- B. SPECIFIC HAZARDS ARISING FROM THE CHEMICAL
  - Lead, lead compounds and sulfuric acid fume may be released during a fire involving the product.
- C. SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS
  - Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing.
- D. FIRE AND EXPLOSION HAZARD

Not flammable.

: Battery may rupture due to pressure buildup when exposed to excessive heat and may be result in the release of corrosive materials.

### 6. ACCIDENTAL RELEASE MEASURES

### A. NECESSARY MEASURES AND PROTECTIVE GEAR TO PROTECT HUMANS

- If a battery ruptures, avoid contact with skin, eyes and clothing. Do not touch spilled material. Use personal protective equipment recommended in Section 8 (Exposure Controls/Personal Protection).
- B. NECESSARY MEASURES TO PROTECT ENVIRONMENT

2

- Notify authorities and appropriate federal, state, and local agencies. Prevent the product from spreading into the environment. Avoid direct discharge into drains.
- C. METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP
  - SMALL SPILLS: Collect all released material in a plastic lined metal container. If necessary neutralize the residue with a dilute solution of sodium carbonate. Wash affected area.
  - LARGE SPILLS: Contain liquid using absorbent material, by digging trenches or
  - by building a dike. Absorb with dry earth, sand or other non-combustible material. Neutralize the residue with a dilute solution of sodium carbonate.
    Dispose of all contaminated materials in accordance with current local regulations.

### 7. HANDLING AND STORAGE

## A. PRECAUTIONS FOR SAFE HANDLING

: Protect from physical damage.

		Control No.	GB-AGM-02
SEBANG	Material Safety Data sheet (MSDS)	Date First	May 16, 2008
SEBANG GLOBAL BATTERY		Date Final	Jan 2021

### B. CONDITIONS FOR SAFE STORAGE (INCLUDING ANY INCOMPATIBILITIES)

Avoid contact with eyes. Store in a cool, dry, ventilated area away from sources : of heat, moisture, incompatibilities, and direct sunlight. Have emergency

equipment (for fires, spills, leaks, etc.) readily available.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- A. OCCUPATIONAL EXPOSURE LIMIT(S), BIOLOGICAL EXPOSURE STANDARD
  - OSHA-PEL 0.05 mg/m3 (Lead), 1 mg/m3 (Sulfuric acid)

ACGIH-TLV TWA 0.05 mg/m3 (Lead), TWA 0.2 mg/m3 (Sulfuric acid)

- **B. APPROPRIATE ENGINEERING CONTROLS** 
  - : Use local exhaust ventilation if necessary to control airborne mist and vapor.

## C. INDIVIDUAL PROTECTION MEASURES

Respiratory protection :	If significant mists or aerosols are generated an approved respirator is recommended. If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection.
Eye protection :	Wear safety glasses with side shields (or goggles).
Hand protection :	Wear chemical resistant gloves. Gloves should be replaced immediately if signs of degradation are observed.
Body protection :	Use good work and personal hygiene practices to avoid exposure. Consider the provision in the work area of a safety shower and eyewash. Always wash thoroughly after handling chemicals.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

A. APPEARANCE (PHYSICAL STATE, COLOUR etc.) : Off-white cloudy liquid with solid object. B. Odour : Characteristics. C. ODOR THRESHOLD : Not available. D. pH pH < 1 (Sulfuric acid) • E. MELTING POINT/FREEZING POINT Not available. ٠ F. INITIAL BOILING POINT AND BOILING RANGE Not available. • G. FLASH POINT : Non-flammable. H. EVAPORATION RATE Not available. I. FLAMMABILITY (SOLID, GAS) : Not applicable. J. UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS : Non-flammable. K. VAPOR PRESSURE : Not available. L. SOLUBILITY : Soluble in water.

				Control No.	GB-AGM-02
SEBANG	Material Safety Dat	a sh	eet (MSDS)	Date First	May 16, 2008
SEBANG GLOBAL BATTERY				Date Final	Jan 2021
M. VAPOR DENSITY					
N. SPECIFIC GRAVITY					
O. PARTITION COEFFIC	CIENT OF n-OCTANOL/WATE	F:	Not available.		
P. AUTO-IGNITION TEM	IPERATURE	:	Not applicable.		
Q. DECOMPOSITION TE		:	Not available.		
R. VISCOSITY	: Not available.				
S. MOLECULAR WEIGH	łT	:	Mixture.		
Note: These physical prop	perties are typical values for t	his pr	oduct.		
A. APPEARANCE (PHYS	SICAL STATE, COLOUR etc.)	:	Bluish white, silve	ry gray.	
B. Odour	: None.				
C. ODOR THRESHOLD	: Not available.				
D. pH	: Not applicable.				
E. MELTING POINT/FRE	EEZING POINT	:	<b>327.5</b> ℃		
F. INITIAL BOILING POI	INT AND BOILING RANGE	:	1740℃ (1013 hPa	a)	
G. FLASH POINT	: Non-flammable.				
H. EVAPORATION RAT	E	:	Not applicable.		
I. FLAMMABILITY (SOL	LID, GAS)	:	Not applicable.		
J. UPPER/LOWER FLA	MMABILITY OR EXPLOSIVE L	IMITS.			
	: Non-flammable.				
K. VAPOR PRESSURE	: 1.33 hPa (973℃)				
L. SOLUBILITY	: Insoluble in water.				
M. VAPOR DENSITY	: Not applicable.				
N. SPECIFIC GRAVITY	: 11.34 g/cm3				
O. PARTITION COEFFIC	CIENT OF n-OCTANOL/WATE	F:	Not applicable.		
P. AUTO-IGNITION TEM	<i>I</i> PERATURE	:	Not applicable.		
Q. DECOMPOSITION TE	EMPERATURE	:	Not applicable.		
R. VISCOSITY	: Not applicable.				
S. MOLECULAR WEIGH	łT	:	207.2		
Note: These physical properties are typical values for Lead(Pb).					

### **10. STABILITY AND REACTIVITY**

- A. CHEMICAL STABILIT: Stable at normal temperatures and storage conditions.
- **B. POSSIBILITY OF HAZARDOUS REACTIONS** 
  - : Hazardous polymerization will not occur.
- C. CONDITIONS TO AVOID (STATIC DISCHARGE, SHOCK, VIBRATION etc.):
  - Overcharging. Sources of ignition. Mechanical impact. Contact with incompatible chemicals.

		Control No.	GB-AGM-02
SEBANG	Material Safety Data sheet (MSDS)	Date First	May 16, 2008
SEBANG GLOBAL BATTERY		Date Final	Jan 2021

D. SUBSTANCES TO AVOID

: If a battery ruptures, avoid contact with organic materials and alkaline materials.

# E. HAZARDOUS DECOMPOSITION PRODUCTS

: Lead, Lead compounds and sulfuric acid fumes may be released during a fire involving the product.

# **11. TOXICOLOGICAL INFORMATION**

Inhalation   :   Corrosive. severe irritation and burns.     Ingestion   :   Serious burns.     Eye/Skin   :   Tearing, redness, swelling, corneal damage, irreversible eye damage ar severe burns.     Skin   :   Redness, swelling, burns and severe skin damage.			
Eye/Skin   Tearing, redness, swelling, corneal damage, irreversible eye damage ar     Eye   : severe burns.     Skin   : Redness, swelling, burns and severe skin damage.			
EyeTearing, redness, swelling, corneal damage, irreversible eye damage ar severe burns.Skin:Redness, swelling, burns and severe skin damage.			
Eye::severe burns.Skin:Redness, swelling, burns and severe skin damage.			
	d		
B. Delayed and immediate effects and also chronic effects from short and long term exposure	effects and also chronic effects from short and long term exposure		
Acute toxicity (possible route of exposure) :			
Oral (LD50): Rat 2140 mg/kg (Sulfuric acid),			
Skin (LD50) : Not available.			
Inhalation (LC50): Rat 0.347 mg/L(4hr) (dust//mist)			
Skin corrosion/irritation : cat 1			
Serious eye damage/irritation : cat 1			
Respiratory sensitization : Not available.			
Skin sensitization : Not available.			
Carcinogenicity : cat 1B			
ACGIH Group A2, IARC Group 1 (Mist containing sulfuric acid) * Note: Sulfuric acid mist is not expected under normal use of the produc ACGIH Group A3, IARC Group 2B (Lead), IARC Group 3 (Polypropylend			
Germ cell mutagenicity : cat 2			
Reproductive toxicity : Not available.			
STOST-single exposure : cat 1			
: Respiratory.			
STOST-repeated exposure : cat 1			
. Hematopoietic system, kidney, central nervous system, peripheral nervo	us		
Aspiration hazard : Not available.			
C. Numeric measure of toxicity (such as acute toxicity estimates) - ATEmix			
Oral (LD50): Rat > 5,000 mg/kg			
Skin (LD50) : Not available.			
Inhalation (LC50): Rat 2.51 mg/L(4hr) (dust//mist)			
10페이지 주 7페이지			



Control No.	GB-AGM-02
Date First	May 16, 2008
Date Final	Jan 2021

## **12. ECOLOGICAL INFORMATION**

- A. Aquatic/terrestrial ecology toxicity
  - Fish (LC50):Not available.Daphnia (EC50):Not available.
  - Algae (EC50) : Not available.
- B. Persistence and degradability
  - Persistence : Not available.
- Degradability : Not available.
- C. Bioaccumulative potential
  - : Not available.
- D. Mobility in soil : Not available.
- E. Other hazardous effects

Not available.

:

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Hazardous wastes must be transported by a licensed hazardous waste transporter and

- : disposed of or treated in a properly licensed hazardous waste treatment, storage, disposal or recycling facility. Consult local, state, and federal regulations for specific requirements.
- B. PRECAUTIONS (INCLUDING DISPOSAL OF CONTAMINATED CONTAINER OR PACKAGE)
  - Since emptied containers retain product residue, follow label warnings even after container is emptied.

## **14. TRANSPORT INFORMATION**

All Global's AGM series are valve regulated lead acid (VRLA) batteries. GLOBAL's VRLA batteries meet test specifications for "non-spillable electric storage batteries", as required by D.O.T., 49 CFR 173. 159(d), and IMO/IMDG, and ICAO/IATA packing instruction 872 and note A67; therefore, are non-regulated when protected against short circuits, kept upright, and securely packaged. The battery and the outer packaging must be plainly and durably marked "NONSPILLABLE BATTERY" or "NONSPILLABLE".

These batteries meet the requirements contained in the following special provisions.

- A. Regulatory Body Special provisions
- B. U. S. DOT Unregulated, meets the requirement of 49 CFR 173.159(d)
- C. IATA / ICAO Unregulated, meets the requirements of Special Revisions A67
- D. IMO IMDG Unregulated, meets the requirements of Special Revisions #238
- \* Proper Shipping Name : Batteries, wet, non-spillable



## **15. REGULATORY INFORMATION**

וח	INVENTORIES	
שו		ed (EINECS No. 231-100-4(Lead), 231-639-5(Sulfuric acid))
	TSCA/US : Lis	
		ed (ENCS No. 1-527(Lead), 1-430(Sulfuric acid))
	AICS/AUSTRALIA : Lis	
	DSL/CANADA : Lis	ed.
	IECSC/CHINA : Lis	ed.
	PICCS/PHILIPPINES : Lis	ed.
	KECI/S.KOREA : Lis	ed (KE-21887(Lead), KE-32570(Sulfuric acid))
۵	International Environmental A	greement
	PIC : No	listed.
	POPs : No	listed.
	Ozone depletion : No	listed.
	EU. Directive 67/548/EEC on the	classification, packaging, and labelling of dangerous substances, Annex I
	Classification : C;	235
	Risk Phrases: R3	
	Safety Phrases : S1/	2, S26, S30, S45
D		vironment) and U.S. Federal, Right-To-Know
	CERCLA Section 103 (40 CF	R 302.4)
	: 10	o (4.535 kg) (Lead), 1000 lb (453.599 kg) (Sulfuric acid)
	EPCRA (SARA Title III) Secti	
		00 lb (453.599 kg) (Sulfuric acid)
	· · · · ·	on 304 (EHS - Reporting Quantities)
		00 lb (453.599 kg) (Sulfuric acid)
	· · · · ·	on 313 - Toxic chemical release reporting
	•	furic acid (acid aerosols including mists, vapors, gas, fog, and other airborne ns of any particle size)
	OSHA Specifically Regulated	Substances (29 CFR 1910.10011052)
	: No	applicable.
٦	CANADA REGULATORY INF	ORMATION
	WHMI	S Ingredient Disclosure List : Regulated.
	product described in the Safety	In given above only indicates the principal regulations specifically applicable to the Data Sheet. The user's attention is drawn to the possible existence of additional regulations. Refer to all applicable national, international and local regulations or

#### **16. OTHER INFORMATION**

A. SOURCE OF DATA :

		Control No.	GB-AGM-02
SEBANG	Material Safety Data sheet (MSDS)	Date First	May 16, 2008
SEBANG GLOBAL BATTERY		Date Final	Jan 2021

Guideline for Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

EC-ECB, International Uniform Chemical Information Database (IUCLID)

Hazardous Substances Data Bank (HSDB)

Registry of Toxic Effects of Chemical Substances (RTECS)

National Institute of Technology and Evaluatio -NITE (Japan).

NFPA 704 Standard System for the Identification of the Hazards of Materials for Emergency Response.

International Chemical Safety Cards(ICSC)(http://www.nihs.go.jp/ICSC)

3E Company/Ariel WebInsight DB.

B. THE DATE OF PREPARATION OF THE MSDS : May 16, 2008

C. THE NUMBER OF TIMES REVISED AND THE DATE OF PREPARATION OF THE LATEST REVISION

: Jan 2021

D. OTHER INFORMATIC:

The above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Sebang Global Battery CO.,Ltd. shall not be held liable for any damage resulting from handling or from contact with the above product. Each individual should make a determination as to the suitability of the information for their particular purpose(s). Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.